

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

APPLICATION FOR LETTERS PATENT

**Context-Aware and Location-Aware Cellular Phones
and Methods**

Inventor(s):

Gopal Parupudi
Stephen S. Evans
Edward F. Reus

ATTORNEY'S DOCKET NO. MS1-695

09746940 422200

1 **TECHNICAL FIELD**

2 This invention relates to generally to the area of context-aware computing
3 or ubiquitous computing.
4

5 **BACKGROUND**

6 The World Wide Web (WWW) was created to make content available from
7 any source in any location around the world. Users of the Web are able to
8 generally access a seemingly infinite number of resources via the Web. The Web
9 has been highly successful in this regard. Yet, with the evolution of the Web,
10 certain needs remain largely unmet. Specifically, people continue to have a need
11 to access information that has a contextual aspect to it. That is, often times,
12 individuals will find themselves in a computing environment that carries with it a
13 certain context. Yet, the context of the environment cannot be easily incorporated
14 into the present computing environment. As an example, consider the context of
15 location. People generally have a need to access information, data, resources and
16 the like, that have geographic dimensions to them. For example, individuals may
17 desire to take advantage of services or products that are close in proximity to
18 where they currently are located. In this regard, it is desirable to understand the
19 individual's contextual location so that services, goods and the like can be made
20 available to the individual. As "eCommerce" continues to grow in importance, the
21 necessity of bringing people, places, services and goods together in an efficient
22 manner will become critically important.

23 To date, many attempts have been made to bring people, places, services
24 and goods together. These various attempts have generally approached the
25 problem from different directions in an often times incompatible manner. As an

1 example, consider the context of location. Some services have attempted to bring
2 people and services together by defining large databases that maintain information
3 about the services. For example, a list of restaurants may be maintained in a web
4 accessible database where each restaurant is associated with a zip code in which
5 the restaurant is located. When a user desires to locate a particular restaurant, they
6 might simply enter the zip code where they are located to see a list of
7 corresponding restaurants in that zip code. From the list of restaurants, they might
8 be able to select one or two restaurants of interest. This approach is undesirable
9 for a number of reasons. First, the operation of the system is dependent upon a
10 central server that is responsible for receiving user queries and executing the
11 queries to return the information to the user. In the event the server fails, so too
12 does the service. In addition, this particular service might be suited to finding
13 restaurants, but possibly not other businesses. In addition, the granularity with
14 which the results are returned to the user may foist some of the search burden on
15 the user (i.e. the user gets a list of restaurants in a nearby zip code, but has to
16 further explore the list to select which ones are of interest). Further, the list of
17 restaurants may include some restaurants that are blocked by some type of a
18 physical barrier (i.e. a river, mountain, etc.) that makes the distance, as the crow
19 flies, unroutable.

20 Providers of services and products want to be connected to nearby end-
21 users. End-users want to consume these services and goods at the closest and
22 most convenient location. Acquiring the services of a dentist or a plumber that
23 lives somewhere "out on the net" is not appropriate if you need them to fill a
24 cavity or unclog a sink. Looking for the nearest hotdog while in a stadium
25 requires you to stay in the stadium.

1 There is an unsolved need to be able to create context-aware computing in
2 which computing devices can participate in their particular context. In specific
3 circumstances, there are needs to provide relational position awareness among
4 physical locations in both public and private views of the world. To date,
5 however, there is no one standardized view of the world that would unlock the
6 potential of context-aware computing. Context-aware computing is much more
7 than just position awareness—although this is a very big field in and of itself.

8 This invention arose out of concerns associated with developing a
9 standardized, context-aware infrastructure and related systems to unlock the
10 potential of context-aware computing.

11 12 SUMMARY

13 Context-aware and location-aware cellular phones and methods are
14 described. In one embodiment, cellular phones are configured to wirelessly
15 receive information that pertains to their current context or location. The phones
16 then automatically use the information to modify one or more cellular phone
17 behaviors, e.g. by turning the phone off, changing the ringer's pitch, or placing the
18 phone in a vibrate mode. In one particular embodiment, various location types are
19 defined and have associated attributes that define a desired cellular phone
20 behavior. One or more transmitters at a location for which a behavior is desired
21 transmit information that pertains to the location's class type. The cell phones can
22 carry an association of class types and their behaviors so that when the phones
23 receive the class type information, they can automatically adjust their behavior.

BRIEF DESCRIPTION OF THE DRAWINGS

Fig. 1 is a diagram of an exemplary computing device that can be used in accordance with the described embodiments.

Fig. 2 is a conceptual diagram of an exemplary Master World and an exemplary Secondary World in accordance with the described embodiment.

Fig. 3 is an exemplary specific view of a Master World and a Secondary World and their relation to one another.

Fig. 4 is a flow diagram that describes steps in a method in accordance with the described embodiment.

Fig. 5 is a flow diagram that describes steps in a method in accordance with the described embodiment.

Fig. 6 is a high level diagram of an exemplary computing device architecture.

Fig. 7 is a somewhat more specific view of an exemplary computing device architecture.

Fig. 8 is a flow diagram that describes steps in a method in accordance with the described embodiment.

Fig. 9 is a flow diagram that describes steps in a method in accordance with the described embodiment.

Fig. 10 is a flow diagram that describes steps in a method in accordance with the described embodiment.

Fig. 11 is a side elevational view of an exemplary location beacon in accordance with one embodiment.

Fig. 12 is a front elevational view of an exemplary cellular phone.

1 Fig. 13 is a block diagram that illustrates certain cellular phone system
2 components.

3 Fig. 14 is a block diagram of an exemplary software architecture in
4 accordance with one embodiment.

5 Fig. 15 is a flow diagram that describes steps in a method in accordance
6 with one described embodiment.

7 Fig. 16 is a diagram of a system in which one or more of the described
8 embodiments can be employed.

9 Fig. 17 is a flow diagram that describes steps in a method in accordance
10 with one described embodiment.

11 12 **DETAILED DESCRIPTION**

13 **Overview**

14 To provide a standardized solution, embodiments described just below
15 provide a uniform definition of the world. The uniform definition is defined in
16 terms of a hierarchical tree of nodes, where each node represents some aspect of
17 the world. Each node is connected to at least one other node by a branch. An
18 exemplary classification of nodes takes place on a physical level (e.g. physical
19 locations such as political entities, infrastructure entities and public places), as
20 well as a non-physical level (e.g. military APOs). This hierarchical nodal structure
21 is referred to as the Master World, and is a standardized view worldwide. Each
22 node of the Master World has various attributes associated with it that assist in
23 context-aware computing. Exemplary attributes include a unique ID, name,
24 geographic entity class, latitude/longitude, relative importance, contextual parents
25 to name just a few. The Master World is useful because it can be used to

1 determine the relative location of a place anywhere in the world and at any
2 definable granularity.

3 Once an individual's location or a place an individual is interested in is
4 determined, various services that reference the location can be offered to the
5 individual based on their location. That is, value is provided by the Master World
6 model in the ability to tie services to nodal locations in the Master World.

7 Building on this concept, two additional concepts add value—the concept
8 of so-called Secondary Worlds and a “geozone.”

9 A Secondary World is a powerful computing mechanism whereby
10 individual entities (such as businesses or organizations) can define their own
11 particular worlds that need not necessarily conform to the Master World view of
12 the world. That is, while the Master World is essentially a physical hierarchical
13 representation of the world, the Secondary Worlds can be physical and/or logical
14 representations of each individual entities' world view. One particularly useful
15 aspect of the Secondary World is that it links, at at least one point, into the Master
16 World. Thus, within any Secondary World, a user's location not only within the
17 Secondary World, but the Master World as well can be determined. Various
18 services can be attached to the nodes of the Secondary World. Based upon a user's
19 calculated position, these various services that are associated with Secondary
20 World nodes can be offered to the user. In addition, because the user's context is
21 determined relative to the Master World, other services that may not be associated
22 with a particular Secondary World can be offered.

23 A geozone is essentially a spatial indexing mechanism by which the Master
24 World is subdivided into individual zones. In the described embodiment, the
25 zones are subdivided through the use of a quadtree algorithm that is dependent on

1 a density function (although many other spatial index approaches can also be
2 used). Once a desired density level is achieved (density might be defined in terms
3 of points of interest per zone), each node on the Master World is assigned a
4 particular geozone. Geozones enable proximity calculations to be computed in a
5 fast and straight forward manner.

6 A useful aspect of the Master and Secondary Worlds are that they are
7 "reachable" from various computing devices such as stationary (i.e. desktop
8 devices) or mobile computing devices (i.e. cell phones, laptops etc.). That is, the
9 Master World (or at least a portion of it) and one or more Secondary Worlds can be
10 either locally maintained on the computing device, or accessed, e.g. via the Web or
11 some other mechanism, so that a user can derive their context. For example, the
12 Secondary World can be downloaded onto the computing device so that a user can
13 derive their context within the Secondary World. Once a user's context is
14 determined from the Master World and one or more Secondary Worlds, a various
15 robust collection of context-aware solutions become available to the user. For
16 example, specific Secondary World services can be offered or Master World
17 services can be offered. Additionally, services from other Secondary Worlds might
18 also be offered since the user's location may be known (or made known) to these
19 other Secondary Worlds. In this way, the Master World can link two or more
20 Secondary Worlds together.

21 Another aspect is that the described embodiments harness the computing
22 power of each computing device in determining the device's location. Here, by
23 virtue of having the Master World and one or more Secondary Worlds reachable
24 by the device (and possibly locally maintained on the device), the device itself
25 determines its own context.

1 One embodiment provides a client side device that is configured to utilize
2 the context-aware structures that are discussed above, i.e. the Master and one or
3 more Secondary Worlds. The Master World or a portion thereof can be locally
4 available on the device or can be accessible at another location, e.g. via the Web.
5 In this embodiment, the client device has a location service embodied thereon.
6 The described location service is a software module that can determine the
7 location of the device and can answer queries from various applications (either
8 executing on the device or off the device). The location service determines the
9 location of the device by using the Master World and one or more Secondary
10 Worlds. The applications query the location service through one or more
11 Application Program Interfaces (APIs) or Events to get location information that is
12 used by the applications to render a service.

13 The location service makes use of one or more location providers that
14 convey information to the device. This information can be information that is
15 specific to the location provider, or can be information that can be mapped directly
16 into a node of the Master World or Secondary Worlds. Exemplary location
17 providers can include Global Positioning Service (GPS) providers, cell phone
18 providers (cell providers), Bluetooth providers, a user interface provider and the
19 like. The location providers provide information that gives some aspect of a
20 device's current location. This information is used by the location service to
21 ascertain the location of the device.

22 One particularly advantageous feature of the client device is a standard or
23 common location provider interface. The location provider interface enables the
24 various location providers to provide information to the location service so that the
25 location service can use the information to determine its location. Essentially, the

multiple location provider interface is a common interface that enables multiple different location providers to provide location information (or hints) about location to a location service that is on a device. The location providers can provide the location information constantly, at intervals, or when polled by the device. The location information can be provided with confidence and accuracy estimates to enable the location service to evaluate the relative quality of the information before it is used. The various providers also have the ability to self-monitor themselves which assists in the providers' ability to intelligently convey information to the location service. By having a common interface, the collection of location providers is dynamically extensible—that is location providers can be added or removed from the collection of location providers without any interference of the functionality performed by the location service or device. The location providers can be added or removed while the device is operating. This is particularly useful in accommodating location providers that are developed in the future. In this particular embodiment, two levels of abstraction are provided i.e. (1) the provider interface that receives information from the location providers and (2) the API/events layer that enables applications to get at the various information.

One focus of this embodiment is a device that can collect context information (e.g. location information) from a variety of different sources, determine the device's current context from that information, and provide the current context at some level to one or more applications that can use the device's context to render a service or enable the device to participate in its context environment.

In the described embodiment, the device receives location information or hints about its location. This information is collated and mapped by the location

1 service into a node in the Master World and/or Secondary World. The hierarchical
2 trees can then be traversed to determine the device's accurate location in both the
3 Secondary World and the Master World. At this point, the device has determined
4 its context. The information that is collected can be subject to arbitration to ensure
5 that only highly trusted information is used to determine context. The location
6 information can be cached to provide "current location information" which, for a
7 definable period of time will be accurate to some degree. Thus, if for some reason
8 other location providers are unavailable, the cache can be used to ascertain
9 location.

10 Once a device's location is determined, the device can apply a security
11 policy to the information. Once this is done, the device can begin to answer
12 queries from various applications.

13 One aspect of the described embodiment is a "favorite locations" aspect in
14 which the device can be automatically configured, when it determines its context,
15 so that it can adjust to the different locations.

16 Further, various types of location providers can convey different types of
17 information. For example, a so-called "thin provider" provides location
18 information that is translated by the location service into the appropriate node
19 information. A so-called "thick provider" includes logic that takes location
20 information and provides it in a form that can map directly into the Master World
21 or Secondary World.

22 In another embodiment location translation services are provided that are
23 directed to determining, as accurately as possible, the context or location of the
24 device. In this embodiment, information is received from the various location
25 providers. This information includes location, accuracy and confidence (all of

1 which are provided by the location provider), trust (which is assigned to a location
2 provider by the device or a user) and a timestamp (which helps to age the location
3 information). The location translation processing involves determining which of
4 the location providers are valid and active. The location providers can be ranked
5 in accordance with the confidence and trust levels. This defines an ordered list of
6 location providers. Provision is made for a situation in which all of the location
7 providers may go inactive. If so, a "current location" is used as a location
8 provider whose confidence decreases over time.

9 In the event that information from two or more of the location providers
10 conflicts, then measures can be taken to use information for which there is a
11 higher level of trust. The information that is provided by all of the location
12 providers (assuming no conflict) can then be used to determine a tree structure and
13 a node's entity ID (EID). The tree might be the Master World and the EID is a
14 node on the Master World. The tree might also be a Secondary World and the EID
15 (or location unique identifier or "LUID") is a node on the Secondary World.
16 Once this information is collected, complete location information can be
17 determined by simply traversing the tree(s). Once a device's location is
18 determined, a cache can be updated with the current location (including a time
19 stamp).

20 In another embodiment, privacy issues in the context-aware computing
21 environment are addressed. In this embodiment, the location service has acquired
22 location information that pertains to the location of a particular device. A privacy
23 manager determines what level of information to provide to applications that
24 might request the information. The privacy manager can reside on the computing
25 device itself, or can be proxied by a trusted third party.

1 According to this embodiment, a scale of privacy levels are defined. Each
2 level is defined to include more or less specific information about the location of a
3 particular device. A user is able to assign a privacy level to entities that might
4 request location information. Additionally, each node of the Master World and a
5 Secondary World can have a privacy level associated with it. When a query from
6 an application is received, the privacy manager first determines who the query is
7 from and the privacy level associated with the application or entity. The privacy
8 manager then evaluates one or more of the Master World and the Secondary World
9 to find a node that has a corresponding privacy level. When a corresponding node
10 is found, information at that particular granularity is provided to the requesting
11 application or entity.

12 In another embodiment systems and methods of providing a location
13 provider in the form of a location beacon are described. In this embodiment, a
14 location beacon is provided that can be mounted in various areas (public/private
15 areas) to beacon the location to any computing devices within transmission range.
16 The information that is transmitted enables a device to determine its location or
17 context. The location beacon can transmit information that is specific to the
18 location service that uses the information. Transmitted information can include an
19 EID/URL pair, and a LUID/URL pair. The EID gives the node identification of a
20 node in the Master World; and, the associated URL gives a protocol to
21 communicate with the Master World. The URL might, for instance, link to a
22 server that can provide additional context information that uses the EID. The
23 LUID indicates a node on a Secondary World that corresponds to a current
24 location; and the URL gives a protocol to communicate with the Secondary World.
25 For example, the URL can link with a server that is hosting the Secondary World.

1 This server can then be queried to discover more information about the Secondary
2 World (i.e. Secondary World tree structure, location of associated resources, etc.)
3 With the EID and LUID (along with the URLs), a device can now traverse the
4 Master World or Secondary World to determine its location. Various technologies
5 can be used to implement the beacon (wireless, RF, IR). The beacon can be a
6 “program once” device to deter tampering. Programmable beacons can, however,
7 be provided. Security can also be provided in the form of a verifiable signature
8 that is provided with the beacon information to assure the veracity of the
9 transmitted information.

10 A useful context-aware computing aspect of the beacon is the concept of
11 “location-enabled access”. That is, in addition to (or separately from) receiving
12 location information, a beacon can transmit code download pointers that enable
13 smart devices to access software code that allows the device to participate in its
14 current context.

15 **Exemplary Computing System**

16
17 In the context of this document, the term “computing device” is used to
18 refer generally to any type of computing device. Characteristics of exemplary
19 computing devices are that they typically include one or more processors,
20 computer-readable media (such as storage devices and memory), and software
21 executing on the one or more processors that cause the processors to implement a
22 programmed functionality. In particular embodiments, implementation takes place
23 in the context of mobile computing devices (e.g. laptop computers and the like),
24 and/or hand-held computing devices (e.g. palm PCs, wireless telephones and the
25 like).

Fig. 1 is a schematic diagram that constitutes but one example of a computing device that is suitable for use in connection with the described embodiments. It is to be understood that portions of the illustrated computing device can be incorporated in one or more of the computing devices (e.g. palm PCs, wireless telephones, etc.) with which particular embodiments are envisioned for use.

Computer 130 includes one or more processors or processing units 132, a system memory 134, and a bus 136 that couples various system components including the system memory 134 to processors 132. The bus 136 represents one or more of any of several types of bus structures, including a memory bus or memory controller, a peripheral bus, an accelerated graphics port, and a processor or local bus using any of a variety of bus architectures. The system memory 134 includes read only memory (ROM) 138 and random access memory (RAM) 140. A basic input/output system (BIOS) 142, containing the basic routines that help to transfer information between elements within computer 130, such as during start-up, is stored in ROM 138.

Computer 130 further includes a hard disk drive 144 for reading from and writing to a hard disk (not shown), a magnetic disk drive 146 for reading from and writing to a removable magnetic disk 148, and an optical disk drive 150 for reading from or writing to a removable optical disk 152 such as a CD ROM or other optical media. The hard disk drive 144, magnetic disk drive 146, and optical disk drive 150 are connected to the bus 136 by an SCSI interface 154 or some other appropriate interface. The drives and their associated computer-readable media provide nonvolatile storage of computer-readable instructions, data structures, program modules and other data for computer 130. Although the

1 exemplary environment described herein employs a hard disk, a removable
2 magnetic disk 148 and a removable optical disk 152, it should be appreciated by
3 those skilled in the art that other types of computer-readable media which can
4 store data that is accessible by a computer, such as magnetic cassettes, flash
5 memory cards, digital video disks, random access memories (RAMs), read only
6 memories (ROMs), and the like, may also be used in the exemplary operating
7 environment.

8 A number of program modules may be stored on the hard disk 144,
9 magnetic disk 148, optical disk 152, ROM 138, or RAM 140, including an
10 operating system 158, one or more application programs 160, other program
11 modules 162, and program data 164. A user may enter commands and information
12 into computer 130 through input devices such as a keyboard 166 and a pointing
13 device 168. Other input devices (not shown) may include a microphone, joystick,
14 game pad, satellite dish, scanner, or the like. These and other input devices are
15 connected to the processing unit 132 through an interface 170 that is coupled to
16 the bus 136. A monitor 172 or other type of display device is also connected to the
17 bus 136 via an interface, such as a video adapter 174. In addition to the monitor,
18 personal computers typically include other peripheral output devices (not shown)
19 such as speakers and printers.

20 Computer 130 commonly operates in a networked environment using
21 logical connections to one or more remote computers, such as a remote computer
22 176. The remote computer 176 may be another personal computer, a server, a
23 router, a network PC, a peer device or other common network node, and typically
24 includes many or all of the elements described above relative to computer 130,
25 although only a memory storage device 178 has been illustrated in Fig. 1. The

1 logical connections depicted in Fig. 1 include a local area network (LAN) 180 and
2 a wide area network (WAN) 182. Such networking environments are
3 commonplace in offices, enterprise-wide computer networks, intranets, and the
4 Internet.

5 When used in a LAN networking environment, computer 130 is connected
6 to the local network 180 through a network interface or adapter 184. When used
7 in a WAN networking environment, computer 130 typically includes a modem 186
8 or other means for establishing communications over the wide area network 182,
9 such as the Internet. The modem 186, which may be internal or external, is
10 connected to the bus 136 via a serial port interface 156. In a networked
11 environment, program modules depicted relative to the personal computer 130, or
12 portions thereof, may be stored in the remote memory storage device. It will be
13 appreciated that the network connections shown are exemplary and other means of
14 establishing a communications link between the computers may be used.

15 Generally, the data processors of computer 130 are programmed by means
16 of instructions stored at different times in the various computer-readable storage
17 media of the computer. Programs and operating systems are typically distributed,
18 for example, on floppy disks or CD-ROMs. From there, they are installed or
19 loaded into the secondary memory of a computer. At execution, they are loaded at
20 least partially into the computer's primary electronic memory. The invention
21 described herein includes these and other various types of computer-readable
22 storage media when such media contain instructions or programs for implementing
23 the steps described below in conjunction with a microprocessor or other data
24 processor. The invention also includes the computer itself when programmed
25 according to the methods and techniques described below.

1 For purposes of illustration, programs and other executable program
2 components such as the operating system are illustrated herein as discrete blocks,
3 although it is recognized that such programs and components reside at various
4 times in different storage components of the computer, and are executed by the
5 data processor(s) of the computer.

6 7 **Defining the World**

8 One of the problems to date with attempting to solve the context-aware
9 computing problem is that every proposed solution has its own approach, data
10 structures, processes and the like. There is little if any standardization between the
11 various approaches. In the described embodiment, standardization is achieved at
12 the foundational level by defining a universal view of the Earth. That is, a
13 universally acceptable definition of the Earth is proposed and is useable in various
14 computing scenarios to enable context-dependent computing. In this document, a
15 specific example of context-dependent computing is given in the form of location
16 dependent computing. It is to be understood that this constitutes but one example
17 of a context in which the various embodiments discussed below can be employed.
18 Other "contexts" can include, any information that can fit into a hierarchical
19 structure including, without limitation, role/personnel in an organization, device
20 categorizations, current activity, current environment, active devices and the like.

21 22 **The Master World**

23 A Master World is defined as a politically correct and publicly accepted
24 hierarchical tree structure that catalogs physical location or geographic divisions
25 of the Earth. The Master World is defined in such a way that many different

1 classes of political, administrative and geographic entities across the entire Earth
2 are included. Areas of political contention are accounted for by presenting a view
3 of the world based on the language/locale of the computing device.

4 Fig. 2 shows an exemplary hierarchical tree structure 200 that represents a
5 portion of the Master World. The Master World contains multiple nodes 202, with
6 each node representing some type of geographic division (e.g. political or natural
7 entity) of the Earth. In the illustrated example, the nodes of the Master World are
8 arranged in the following groups: (1) political or natural entities (e.g. continents,
9 countries, oceans, states, counties, cities and the like); (2) infrastructure entities
10 (e.g. postal codes, area codes, time zones and the like); (3) public place entities
11 (e.g. parks, malls, airports, stadiums, and the like); and (4) non-physical entities
12 (military postal code regions, vacation regions, affiliate coverage areas of
13 television networks that can be geographically discontinuous, and the like).

14 In the Fig. 2 example, the top node of the tree structure represents the
15 Earth. Each node underneath the top node represents a geographical division of
16 the Earth. In this example, none of the nodes have an association with any
17 businesses or services. That is, there is a distinction between node entities that are
18 part of the Master World and non-geographic places where activities take place.
19 Though the Master World includes nodes for public places (i.e. airports, malls,
20 etc), it does not include individual listings of businesses or service providers.
21 Each node is uniquely identified by an ID (EID or entity ID). In addition to the
22 unique EIDs, a URL is associated with the tree structure and provides a context for
23 the tree structure as will become apparent below.

24 As an example, consider the following: Seattle-Tacoma International
25 Airport (SeaTac) will be included in the Master World, but references to individual

1 airline business locations at SeaTac might be "leaves" on the tree that are tagged
2 by the SeaTac Airport EID (see "Secondary World" section and the Table below).
3 Similarly, the Seattle Center might be a node on the Master World, while the
4 Seattle Arts Festival, Bumpershoot, the Seattle Sonics NBA Team, and the Seattle
5 Center Starbucks Coffee Shop might be tagged with the Seattle Center EID. As
6 another example, the Master World also contains nodes for all Interstate
7 (motorway) exits. For example, the I-90, Exit 109, Washington is a node in the
8 Master World. The Best Western Inn located at 1700 Canyon Road in Ellensburg,
9 Washington might be tagged with the EID of this Exit.

10 Thus, the Master World provides a uniform way of defining locations. The
11 uniform location definitions can then be universally used to assign attributes to
12 goods or services. Whenever a computing device determines its location to
13 correspond to a particular uniform location definition, it can take advantage of the
14 location-dependent goods or services that share the uniform location definition.
15 The Master World is useful because it is a standardized view of the world. Its
16 accurate standardized geographic dimension attribution can be easily accessed by
17 both providers and consumers. Services and product providers (or third parties
18 such as search engines, network and yellow-page database directories) can use the
19 nodes of the Master World by assigning a standardized persistent geographic
20 reference to all commerce locations or points of interest. These commerce
21 locations or points of interest can be considered as "leaves" on the tree structure.

22 In the illustrated example, the nodes of the Master World have one or more
23 attributes that facilitate its use. Exemplary attributes are described in the table
24 immediately below:
25

Attribute	Description
Entity ID (EID)	The EID is a unique ID for each node. No two nodes have the same EID.
Name	The name is defined in terms of the neutral ground truth (NGT) name. The NGT name supports various language translations for entity names as appropriate (e.g. Pacific Ocean, Pazifischer Ozean, Oceano Pacifico, etc.)
Geographical Entity Class (GEC)	The GEC is a geographical classification of each node. An exemplary GEC is discussed below in the "Geozone" section.
Latitude	The horizontal coordinate position on the globe (i.e. the coordinate position of the node's centroid)
Longitude	The vertical coordinate position on the globe (i.e. the coordinate position of the node's centroid)
Relative Importance	The geographic importance of an entity in reference to other entities in the same region. Value from 1 to 256 (e.g. New York City = 3, Los Angeles = 4, and Omaha = 5 even though Omaha is much smaller but almost as important in relation to surrounding populated places)
Contextual Parent(s)	The parents of the parent/child relationship for each node. Multiple parents are supported (e.g. Redmond is a child of King County, Area Code 425, the Pacific Time Zone, and the MSNBC affiliate KING TV).
Source	The source of origin for the record (e.g. Microsoft or a specified data vendor)
Start Date	Date when the node information was first valid
End Date	Date when the node information was last valid (retired zip codes, breakup of countries)
Modification Date	Records date changes that are made to the record relating to retirement or updates to any fields
Status	Active, lashed (links duplicate nodes together), pending or retired

The attributes listed above constitute exemplary attributes only. Other attributes that are different from and/or additional to those referenced above could be used. A few exemplary entity or node records that employ the above attributes are shown below:

Entity ID (EID)	24948
Name	Pacific Ocean, Pazifischer Ozean, Oceano Pacifico, etc.
Geographical Entity Class (GEC)	138/Ocean
Latitude	0 (+000° 00' 00")
Longitude	-170 (-170° 00' 00")
Relative Importance	1
Contextual Parent(s)	World
Source	MSFT GeoUnit
Start Date	0/0/00

End Date	0/0/00
Modification Date	01/18/00
Status	Active

Entity ID (EID)	27490
Name	Redmond
Geographical Entity Class (GEC)	78/non-capital town
Latitude	47.6768303 (+047° 40' 36")
Longitude	-122.1099625 (-122° 06' 35")
Relative Importance	107
Contextual Parent(s)	<ol style="list-style-type: none"> 1. King, second level [Washington, United States] 2. Puget Sound-Seattle, travel region [Washington, United States]
Source	MSFT GeoUnit
Start Date	0/0/00
End Date	0/0/00
Modification Date	01/18/00
Status	Active

The Master World also serves as a repository of common denominator links between itself and various "Secondary Worlds" and as a conduit that connects Secondary Worlds to other Secondary Worlds. Content, service and device providers can use the Master World to associate their publicly available offerings with a geographic location and the corresponding multiple branch hierarchical structure. This location will be associated with a single entity within the tree structure thereby allowing geographic and time/distance calculations and the necessary parent/child relationship navigation.

The Master World Index (Geozones)

By definition, the Master World provides a hierarchical structure of entities (nodes) that cover the entire globe. Upward navigation within the hierarchy is quite natural. Efficient navigation downward requires geographic proximity awareness. Additionally, there are possible scenarios that will require jumping from branch to branch in order to successfully return values in a query, or for more accurate calculations of distances to close "leaves" attached to nodes other than the original source node. The Master World makes use of an index scheme that can identify peer level nodes by virtue of the geographical proximity. This indexing scheme makes use of a quad tree algorithm to define so-called "geozones."

A quadtree is essentially a spatial index that breaks coverage into homogeneous cells of regularly decreasing size. Each quadrant of the tree has up to four children. The quadtree segmentation process can continue until the entire map is partitioned based on many different end result criteria including the density of the number of items (e.g. points of interest) in each quad. The approach provides a form of spatial index that accelerates spatial selection and content identification.

To complete the spatial indexing scheme to provide each node with a defined geozone, a quadtree algorithm is applied to the nodes and can be based upon a desired density of, for example, points of interest that are to occur in any one zone. Once all of the zones have been defined, each zone is given a unique ID (e.g. top/left and bottom/right Latitude and Longitude pairs). Each of the nodes of the Master World is then assigned a zone in which it is located. Quadtree algorithms are known and will be appreciated by those of skill in the art.

The Master World Location

As can be appreciated, having a uniform standardized representation of the world in the form of a hierarchical traversable tree structure can greatly facilitate the manner to which context-dependent, and more specifically, location-dependent goods and services can be linked.

In the described embodiment, a computing device has access to at least a portion of the Master World. For example, the computing device can have the Master World saved in an internal storage device, it can comprise part of the computing device's operating system, or the device might access the Master World via a network medium such as the Internet. With the Master World tree structure being accessible to each computing device, each device has the power to determine its own context or node-referenced location. That is, the computing device can determine, through software it is executing, its particular location, i.e. node. Once the computing device determines an associated node, it can simply traverse the tree to ascertain its complete location.

For example, if a computing device determines that it is currently located at a node that corresponds to the City of Redmond, it can traverse the Master World tree structure to ascertain that it is in the State of Washington, Country of The United States, on the continent of North America. By ascertaining its precise location, the computing device (or its user) is now in a position to take advantage of location-dependent services that might be offered. This particular model is a tremendous improvement over current models that utilize a central server to ascertain location for a number of different devices. In that model, each device (or user) provides information about its location (e.g. perhaps the user enters the zip

code or city that the device is currently in) and might enter a query to find, for example, a McDonald's restaurant in his zip code. The server then takes this information and might, for example, tell the user about the location of all of the McDonald's restaurants within that zip code or city. If the servers fails in this model, then none of the computing devices can take advantage of its services. In the present model, each computing device is self-sustaining. Each can determine its own location, and accordingly, each device can take advantage of location-dependent services. For example, if the computing device understands that it is located on a particular node of the Master World, then it can execute queries to find a McDonald's that has an EID that corresponds to the particular node in which the computing device is located. Particular robustness is provided through the use of the above-described geo-zones. The geo-zones enable proximate geographic divisions to be quickly searched in an efficient manner. For example, if an individual is looking for the nearest Kinko's to make copies and none are located in the geo-zone that corresponds to the node in which the computing device is located, then adjacent geo-zones can be quickly searched.

Secondary Worlds

In the described embodiment, the concept of a Secondary World is used to provide support for additional context. A secondary world might be defined by a third party organization or company and contains nodes that comprise physical and/or logical entities that are unique to that organization. The nodes of the Secondary World may or may not have much context outside of the particular organization that defined the Secondary World, since a secondary world could be made either public or private. The Secondary Worlds do not duplicate the Master

1 World, but rather supplement it in a unique, organization specific manner. While
2 the Master World is defined to be a widely accepted standard, each Secondary
3 World can be a widely variant representation of an organization's proprietary view
4 of the world. In the described embodiment, each Secondary World has at least one
5 node that is linked with a node of the Master World. This gives the Secondary
6 World a context or location in the Master World. Also note that in some context
7 applications, several secondary worlds may be accessed, each providing additional
8 context specific pieces of location data.

9 Fig. 2 shows an exemplary Secondary World 204 that comprises a plurality
10 of nodes 206. Each of the nodes 206 constitutes a physical or logical entity. For
11 example, the nodes can constitute a company, its divisions, regions campuses,
12 buildings, floors in various buildings and rooms on various floors. At least one of
13 the nodes is linked with a node of the Master World. The nodes of the Secondary
14 World can have the same attributes as the nodes of the Master World.

15 As an example of a Secondary World, consider that Boeing might define a
16 Secondary World that includes a list of entities that are important to its employees.
17 The root entity would be "Boeing Corp." and its children might be company
18 divisions (St. Louis Military Division, Everett Plant, Corporate HQ, etc.). Further
19 down the tree structure, individual nodes might be defined to represent individual
20 buildings (Hanger 12), offices within this building (Office 1001), building areas
21 (Southwestern quadrant of hanger 12), etc. Each entity or node has a unique
22 identifier (Local Unique ID or "LUID") and a URL that is associated with the tree
23 on which the node occurs. The URL uniquely identifies the Secondary World tree
24 structure so that a user within that world can determine how to interact with the
25 world. This aspect is discussed below in more detail. Boeing can then use the

1 LUIDs to associate equipment, services, departments or even personnel to a
2 physical or logical location.

3 As a more concrete example, consider Fig. 3 which shows an exemplary
4 portion of the Master World 300 and a Secondary World 302. Master World 300
5 includes the following nodes: World, United States, Washington, Redmond, and
6 Zip = 98052. The exemplary Secondary World 302 is a hierarchical tree structure
7 that has been defined by Microsoft Corporation and includes the following nodes:
8 Microsoft, Redmond Campus, 1 Microsoft Way, Building 26, 3rd floor, Conference
9 Room 3173, Building 24, 2nd floor, Conference Room 1342. In this example, the
10 Secondary World 302 "touch points" into the Master World from the Redmond
11 node. In this example, a video projector is shown as being associated with the
12 node "Conference room 1342". Here, the video projector is not a node in the
13 secondary world. Rather, the video projector is an item in some other resource
14 discovery service (e.g. the active directory) and includes a location attribute that is
15 a pointer to "Conference room 1342." There may be times, however, when nodes
16 can be created in the worlds to represent the location of key services—the node
17 themselves, however, would not represent the services.

18 Like the Master World, the Secondary World is advantageously accessible
19 to a user's computing device. It could, for example, be downloaded—completely
20 or partially--and stored on a storage device and accessed when needed. It might
21 be downloaded for a one time use only. The Secondary World enables the
22 computing device to ascertain its context within the Secondary World. In this
23 example, the computing device would, by using the Secondary World, compute its
24 location within the Secondary World. The computing device can do this by
25 traversing the tree structure from the node in which it is currently located to the

1 root node. This would, for example, give the computing device (and hence the
2 user) a complete Secondary World context. Once the Secondary World location is
3 known, the user is in a position to take advantage of goods or services that are
4 associated with the nodes of the Secondary World. That is, once the computing
5 device determines its Secondary World context, it is ready to become an active
6 participant in the Secondary World.

7 Tremendous value can be achieved by associating goods or services with
8 the individual nodes of the Secondary World. For example, Conference Room
9 1342 has a video projector associated with it. That is, the location of the video
10 projector is in Conference Room 1342. Assume that an individual in Conference
11 Room 3173 has a presentation that requires the use of the video projector such as
12 the one located in Conference Room 1342. Normally, an individual would have
13 no way of ascertaining the location of the video projector other than perhaps
14 physically calling over to the building to check whether there is a video projector
15 available. In this example, because the user's computing device is able to
16 ascertain its location within the Secondary World, it is able to locate the video
17 projector in Conference Room 1342. It would do this by simply executing
18 software that traverses the Secondary World tree structure to find the resource of
19 interest.

20 Note also that because there is a link into the Master World, the computing
21 device is able to derive its context (location) within both worlds. This enables the
22 computing device, and hence the user, to take advantage of goods and services that
23 are associated with the Secondary World, as well as participate in location-
24 dependent services that are consumable based upon the user's location in the
25 Master World.

1 Fig. 4 is a flow diagram that describes steps in a method in accordance with
2 the described embodiment. The steps described just below are implemented by a
3 computing device which, in the illustrated example, is a hand-held mobile
4 computing device.

5 Step 400 accesses first and second hierarchical tree structures that are
6 resident on a computer-readable media. In this example, the tree structures might
7 be stored on the device or might be accessible via a network such as the Internet.
8 An exemplary first tree structure is the Master World and an exemplary second
9 tree structure is a Secondary World. Alternately, the tree structures could both be
10 Secondary Worlds. Once the tree structures have been accessed by the device,
11 step 402 traverses multiple nodes of the tree structures to derive the context of the
12 computing device. In this example, the computing device receives information
13 that informs it as to its location at a node of one of the trees. This information can
14 come to the computing device in any suitable way, e.g. a user can enter the
15 information through a User Interface (UI) or the location might be broadcast to the
16 computing device by another computing device (e.g. through the use of Bluetooth
17 technology or Universal Plug and Play (UpnP). Specific examples of how this
18 information can be conveyed to the computing device are given below in more
19 detail. Regardless of how this information is conveyed to the computing device,
20 once the computing device has the information, it executes software that traverses
21 one or both of the tree structures to derive its context which, in this example, is the
22 device's location.
23
24
25

Defining Secondary Worlds

As was mentioned above, one particularly valuable aspect of the described embodiment is that individual organizations can define their own Secondary Worlds. This gives the organization a great deal of flexibility in providing goods and services and, more broadly, increasing the efficiency of their organization. In one embodiment, a software tool is provided that enables individual organizations to define and maintain their own Secondary Worlds.

In one embodiment, each secondary world can be uniquely identified as a name space (e.g. an XML namespace). This ensures that any overlap in names between the Secondary World and the Master World will not result in a collision. As an example, consider the following: the Master World might contain an entity identified as "Chicago" referring the city. A Secondary World that is established by the National Basketball Association (NBA) and a different Secondary World that is established by the Caterpillar Corporation might also have entities named "Chicago" that refer to completely different entities than the Master World's "Chicago." For example, the NBA's "Chicago" might refer to an NBA market area while Caterpillar's "Chicago" might refer to a sales district. Having the namespace separation between the Master and Secondary Worlds can ensure that there not a collision between identically named entities because each name space is uniquely different from every other namespace.

Fig. 5 is a flow diagram that describes steps in a method of building a context-aware data structure. These steps are implemented by a software tool that is executing on a computing device.

Step 500 receives input from a source that specifies information that pertains to physical and/or logical entities. In this example, a system administrator

1 might physically enter information about the structure of the Secondary World that
2 they desire to define. This information can include information about buildings,
3 divisions, conference rooms and the like. Step 502 then processes the information
4 to define a hierarchical tree structure that has a context. In this example, the
5 context is location. It will be appreciated, however, that other contexts could be
6 employed. Each of the nodes in the hierarchical tree structure represents a
7 separate physical or logical entity. Step 504 then links at least one of the nodes of
8 the hierarchical tree structure with another tree structure having a context. In this
9 example, this other tree structure can comprise the Master World. Once the tree
10 structures have been built and linked, they are ready for traversal in a manner that
11 enables context to be derived from one or more of the nodes.

12 13 **Location as a Service**

14 In the above examples, the computing device is able to determine its own
15 location. In the embodiment about to be described, the computing device
16 determines its location by using location information that is provided to it from a
17 number of different sources of information. The device is able to take the
18 information that is provided to it and process the information to determine a
19 particular node on one or more hierarchical trees. Once the device has done this, it
20 can determine its complete location which is a useful thing to know particularly
21 when there are location-dependent services that can be consumed by the device's
22 user.

23 Fig. 6 shows a high level diagram of an exemplary computing device 600
24 that comprises, among other components, a context service module 602 and one or
25 more context providers 604. The context service module 602 can be implemented

1 in any suitable hardware, software, firmware or combination thereof. In this
2 particular example, the context service module is implemented in software that is
3 executed by one or more device processors. The context service module 602
4 receives context information from one or more context providers 604 and
5 processes the information to determine a current device context. In this particular
6 example, the device context is the device's location. Accordingly, the context
7 providers are location providers that provide location information, in various
8 forms, to the context service module 602 for processing. The location providers
9 604 receive information from various sources of context information (location
10 information) 606.

11 In the context of this document, a context provider comprises a software
12 component that can either be implemented on the device or off the device. The
13 context provider can also include any suitable hardware, firmware or combination
14 thereof. The role of the context providers are to receive information from sources
15 606 and convey the information to the context service module 602 so that the
16 context service module can use the information to determine a current device
17 context.

18 In the case where the context of the device is the device's location, sources
19 606 provide various information to the location providers 604 that pertains to the
20 device's current location. As an example, the sources of the information can
21 include various information transmitters such as a GPS system, cell phone or cell
22 ID, wireless transmitters that transmit location information, location beacons,
23 802.11 transmitters and various other sources of information. The sources of
24 information can also include other computing devices that might, for example,
25 provide location information through Bluetooth technology. In addition, a source

1 of information 606 might include a person who, for example, physically enters
2 location information into the device 600 so that the device can process the
3 information to determine its location.

4 When the device 600 receives the location information from the sources
5 606, it processes the information with the location providers 604 and provides the
6 information to the location service module 602. The location service module 602
7 processes the location information and determines a particular node on one or
8 more of the hierarchical tree structures to which it has access which corresponds to
9 its current location. The location service module 602 can then traverse the tree
10 structures to determine a complete location for the device. Once the complete
11 location is determined, the device 600 can begin to interact with one or more
12 applications 608 that can query the device about its particular location so that one
13 or more location-dependent services can be rendered to the device. In this
14 example, the applications 608 are illustrated as being separate from the device. It
15 is to be understood, however, that the applications could be executing on the
16 device, e.g. a browser application.

17 As shown, the applications 608 can make calls to the device to ask the
18 device where it is located. The device is configured to receive the calls and
19 respond in an appropriate manner to the application. Once the application has the
20 device's location information, it can then render location specific services to the
21 device.

22 **Consider the following example:** You are a traveler and have a hand-held
23 mobile computing device that contains a Master World tree and a Secondary
24 World tree for SeaTac International Airport. You are scheduled to depart on a
25 plane for China from Concourse C. SeaTac International Airport has designed its

1 Secondary World to have the following nodes: "Arrivals", "Departures",
2 "Concourses", "Airlines", "Gates assigned to Airlines", and "Gate Location".
3 When you arrive at the airport, as you enter the airport your computing device
4 receives location information from different sources and with that information
5 your device determines that your location is in the Arrivals node. SeaTac
6 International has bank of servers that are executing applications to assist you while
7 you are in the airport. There are applications that can help you find services,
8 locate facilities (e.g. coffee shops, restaurants), give directions (e.g. how to get to
9 your departure gate), update you on the status of your flight, and even check you
10 in automatically for your flight. Consider also that as you walk through the airport
11 your location changes. Your computing device, however, can receive continuous
12 location information updates so that it can continue to determine its location as
13 you move through the airport. At one point, as you pass a Starbucks coffee shop,
14 your hand held device notifies you that if you purchase a latte at Starbucks and
15 present your hand held device, you will receive a 50 cent discount on your latte.
16 In this example, the utility of the Secondary World is demonstrated. By knowing
17 where its particular customers are in its facility, SeaTac International is able to
18 provide a host of services that were not possible before.

19 Assume further that you are in the airport and your flight is canceled. You
20 must find a place to stay for the night. Accordingly, you wish to determine the
21 closest Double Tree hotel because you really like the warm chocolate chip cookies
22 they give you when you check in. You execute a search engine on your computing
23 device to find the nearest Double Tree hotel. The search engine application first
24 determines your current location in the Master World as indicated by the EID of
25 the Master World node that corresponds to your location. Executing a search, the

1 search engine application looks for a Double Tree hotel that has an attribute that
2 includes an EID that matches your EID. If it finds one, it simply indicates for you
3 the result. If it does not find one with the corresponding EID, it can use an
4 adjacent geozone to search for a Double Tree hotel. It may also provide driving
5 directions to the hotel. The search engine application was able to do this because
6 it was able to ascertain your location in the Master World. It did this quickly and
7 automatically with little or no effort from you.

8 Consider further that as you are driving from the airport to the hotel you
9 decide that you want to find the nearest Kinko's so that you can print 100 copies of
10 a presentation that you are to give in the morning. Consider that your hand-held
11 computing device is a cellular phone and that Sprint is the carrier. Sprint has
12 defined its own Secondary World that might, for example, be designated in terms
13 of cell nets. By virtue of having Sprint's Secondary World on your computing
14 device, you are able to ascertain your location in Sprint's Secondary World and,
15 accordingly, your location in the Master World. Consider that Kinko's also has a
16 Secondary World that links with the Master World. By executing a search
17 application on your device, you are able to ascertain the location of the nearest
18 Kinko's as well as driving directions thereto. All of this is possible because your
19 device has access to the Master World and one or more Secondary Worlds. In this
20 example, the Master World provides a mechanism to daisy chain two or more
21 Secondary Worlds together. This is possible because the Secondary Worlds have
22 at least one reference or link into the Master World.

Exemplary Device Architecture

Fig. 7 shows computing device 600 in somewhat more detail. In this particular embodiment, device 600 comprises an architecture that includes the following components: a location service module 602, a location provider interface 700, an application program interface (API)/Events module 702, a privacy manager 704 a location conversion module 706, one or more applications 608 and one or more location providers 606. Also included in the architecture is an active directory 708, Web service 710, location database 712, and personal places 714. The architecture can be implemented in any suitable hardware, software, firmware or combination thereof. The architecture mentioned above is advantageous in that it enables each computing device to determine its own context or location.

Common Location Provider Interface

One particularly advantageous aspect of the described embodiment is that it employs a common interface 700 that provides a standard interface through which the location providers 606 communicate. By having a common interface, the location providers are extensible (to support future providers) in that they can be dynamically added or removed from the collection of location providers. All that is required of a particular location provider 606 is that it be written to support the common interface.

In this example, there are several location providers 606. These location providers provide location information in different forms. For example, a GPS location provider might provide location information that is GPS specific. Similarly, an IP/Subnet location provider might provide information that is

1 specific to an Internet Protocol. A mobile phone location provider might provide
2 location information in the form of a cell ID. In addition, a location User
3 Interface (UI) might provide location information in the form of a user entry that
4 specifies a city, street or building. All of the location information that is provided
5 by the various location providers is processed by the location service module 602
6 so that a current device location can be determined. To determine the current
7 device location, the location service module 602 may have to consult with an
8 active directory 708, a Web service 710, or a location database 712. In the
9 illustrated example, the active directory 708 might, for example, maintain a
10 secondary world and other networking metadata such as subnet and "site"
11 information that can help determine location based on networking connectivity.
12 Web service 710 can hold the master or secondary worlds, the attributes of which
13 can be used to find location. For example, if a cell phone knows its cell tower ID,
14 then the location provider can query the secondary world to ascertain the nodes
15 that match that cell tower ID. Location database 712 is basically a version of the
16 web service that is hosted or cached locally.

18 **Location Providers**

19 As indicate above, the architecture contemplates multiple different location
20 providers that can provide location information to the location service module 602.
21 This information can come in many different forms and quality levels. The
22 information is then processed by the location service module 602 to determine a
23 current device location. To do this, the service module 602 ascertains from the
24 location information a particular node ID (EID and/or LUID) and a URL that is
25 associated with the tree structure with which the node is associated. Once the

1 location service module ascertains a node ID, it can then query the tree structure
2 (or more accurately a server that manages the tree structure) using the URL to
3 ascertain more information about the tree structure. For example, if the location
4 service module 602 ascertains a LUID from a particular Secondary World, it might
5 then query an active directory 708 (or an Intranet server—which is another
6 location database) to discover the parents and the children of the node. This would
7 then enable the location service module to build the Secondary World.

8 The location providers 606 can provide the location information to the
9 location service module 602 in many different ways. For example, some location
10 providers 606 may continuously provide information (e.g. the GPS provider may
11 continuously provide GPS coordinates). Alternately, the location providers can
12 periodically provide location information such as at specific times or on the
13 occurrence of definable events. For example, a user may define specific times
14 when the location information should be updated. Alternately, the location
15 information might be updated only when a device's location changes (i.e. a
16 location change event). Additionally, the location providers might provide
17 location information when polled by the location service module 602. For
18 example, the location service module 602 can call the location provider interface
19 700 and request location information from one or more of the location providers.

20 One specific location provider 606 is shown as a cache. The cache provider
21 essentially maintains a current device context or location. That is, once the
22 location service module 602 has ascertained its current location, it writes this
23 location to a cache. This enables the device 600 to ascertain its location with a
24 degree of confidence in the event all of the other location providers are not able to
25 provide location information (e.g. the GPS provider may not receive GPS

1 information because the GPS transmitter that supplies it with the information is
2 unable to contact a requisite number of satellites).

3 4 **Confidence and Accuracy Parameters**

5 One important and useful feature of the described embodiment is that one
6 or more of the location providers are configured to assign confidence parameters
7 and/or accuracy parameters to the information that they provide to the location
8 service module 602. Confidence parameters provide a measure of a provider's
9 confidence in the information that it provides to the location service module 602.
10 For example, assume that a GPS transmitter must receive information from five or
11 more satellites in order to provide highly confident information. Assume that only
12 three satellites are available at the time. The GPS transmitter would then transmit
13 its information based only on the three satellites. The GPS provider would then
14 know that the information it receives from the GPS transmitter was based only on
15 three satellites rather than the desired five or more. In this case, the GPS provider
16 can set a confidence parameter on the location information that indicates that it has
17 a lower confidence level than if the information were based on the desired five or
18 more satellites. In this case, the location service module 602 can take the
19 confidence parameters for all of the location providers into account when
20 determining the location of the device. This is discussed in more detail below.

21 With respect to the accuracy parameters, consider that the location
22 information that is received from the location providers is accurate to varying
23 degrees. Some information may be accurate to within one mile, while other
24 information may be accurate to within 100 feet. The location providers are
25 desirably configured to assign accuracy parameters to the location information that

1 they provide to the location service module 602. The accuracy parameters give
2 the location service module an indication of the accuracy of the information.

3 When the confidence and accuracy parameters are used by the location
4 service module 602, the module can make decisions on how to use the location
5 information it receives from each provider. For example, the location service
6 module 602 might disregard completely any information that has a low confidence
7 parameter. It might, on the other hand, strike a balance between the accuracy of
8 the information and its confidence. For example, the module 602 might be
9 programmed to use information with lower levels of accuracy only when there is a
10 high level of confidence in the information. The module 602 might utilize the
11 parameters to assign weights to the information so that the location is calculated as
12 a weighted function of the confidence and accuracy of the information.

13 Another use of the confidence parameters is as follows: Assume that the
14 location service module has determined a device location and has written that
15 location to a cache. At the time when the location is written to a cache, it is
16 assigned perhaps a high confidence level. Assume further that all of the other
17 location providers are unavailable to provide location information. For a period of
18 time, the location service module 602 can use the cache location as a current
19 location and be fairly confident that its information is generally accurate. In this
20 case, the location service module might assign a linearly decreasing confidence
21 level to the information over time so that at some point, it ceases to use the
22 information or informs the user that the information cannot be guaranteed.

Location, Trust, and Timestamp

When the location providers provide their information to the location service module 602, the information can include, in addition to the confidence and accuracy parameters, the actual location information in a known format, a trust parameter and a timestamp. The trust parameter is a metric that is assigned by the location service module 602 to one or more of the location providers and defines the trust that the location service module has for the particular location provider. The timestamp is a metric that defines the time when the location information was provided by the location provider. This assists the location service module 602 in ascertaining whether information is stale and might need refreshed.

Once the location service module 602 has all of the location information, it can then set about determining the location of the device.

Fig. 8 is a flow diagram that describes steps in a method of determining a device context which, in this example, is the device location. These steps are implemented by the location service module 602.

Step 800 gets the current device context. The current context can be the last calculated device context that is stored in the cache. Step 802 determines whether any of a number of context providers are available to provide context information. The location service module might do this by polling the context providers to ascertain which of the providers are active and valid. Step 804 determines whether all of the providers are inactive. If all of the providers are inactive, step 806 decreases the confidence in the current context over time and uses the current context as the device context. Step 802 then continues to monitor for current active and valid providers. If step 804 determines that one or more of the context providers are active, then step 808 orders the active and valid context

1 providers. When the location service module 602 orders or sorts the context
2 providers, it does so as a function of the confidence of the provider's information
3 and/or the trust that the location service module has in the location provider. This
4 provides a ranked list of the location providers. Step 810 checks to ascertain
5 whether the context information appears to be correct. For example, where the
6 context is the location of the device, the location service module 602 might know
7 that five seconds ago the current location was Redmond, Washington.
8 Accordingly, location information that indicates that the current location is
9 Beijing, China would be incorrect. Step 812 then determines whether any of the
10 context information conflicts with either the device's current context or the context
11 information from other providers. For example, the location service module 602
12 can compare the context information from each of the context providers with the
13 information in the cache. If any of the information conflicts with the cached
14 information, then the information from that context provider can be discarded.
15 Similarly, if context information varies inordinately as between the context
16 providers, then step 814 can select the context providers having a predefined level
17 of trust and perhaps use just their information (Step 816). If there are no conflicts,
18 then step 816 determines the current context based upon the information that is
19 provided by all of the context providers. In the described embodiment, this step is
20 implemented by using the information to map to a particular node in one or more
21 of the hierarchical tree structures mentioned above. For example, the location of
22 the device can be ascertained by mapping the information to a particular node, and
23 then completely traversing the tree structure until the root node is reached. Step
24 818 then updates the current context by perhaps writing it to the cache and returns
25 to step 802 to determine the active and valid context providers.

1 The method described above provides a way for the location service
2 module to receive location information and use only the location information that
3 appears mostly likely to represent a current location. Conflicting information can
4 be discounted or disregarded thereby assuring that only the most trusted, accurate
5 and confident information is utilized to determine the device's current location.

6 7 **Self Monitoring**

8 In addition to the confidence and accuracy parameters, one or more of the
9 location providers are advantageously programmed to self monitor their own
10 operation for various irregularities that can occur. On the occurrence of an
11 irregularity, the location providers are configured to notify the location service
12 module 602. For example, the source from which the location provider receives
13 its information may go off line for a period of time so that the location provider is
14 unable to receive any additional information. In this case, the location provider
15 might generate a "provider out" message and send it to the location service
16 module 602. When the location service module 602 receives the "provider out"
17 message, it can then take steps to exclude the location information from that
18 provider from any location calculations that it performs. When the location
19 provider's source comes back on line, it can generate a "provider on" message that
20 informs the location service module 602 that it is able to transmit location
21 information to the module. Of course, the location service module can be notified
22 by the location providers on the occurrence of other operational irregularities, with
23 the above example constituting but one specific case.

Applications

Once the location service module 602 has determined the device's location, it can receive queries from one or more applications 608. In the Fig. 7 example, the applications include a web site application, an Outlook application, and a service discovery application. In the present example, the web site application can be any web site application that is capable of rendering location-specific services. For example, the user of the device 602 might access Amazon.com's web site to buy a favorite book. When the user purchases their book, Amazon.com must now compute the taxes that the user must pay. In this example, a script executing on Amazon.com's web site might query device 602 to learn of the user's location. In this particular example, the device might respond to the query by returning the state in which the user is making the purchase. Amazon.com can then assess the tax automatically. Amazon.com might also desire to know where the individual is located so that they can select an optimal shipping method (UPS or Express Mail). Depending on where the individual is located, one method may be preferred over the other. The Outlook application might query the location service module to ascertain the location because it (or the operating system, e.g. Windows) may change device settings based on the location of the computing device. For example, the user may print on one particular printer while at work, and another particular printer when at home. When the Outlook application determines that the user has gone home for the day, it can automatically change the device settings for the printer at the user's home. It might acquire the print settings from a personal places data store 714. Thus, the device is automatically configured for use depending on the user's location. The service discovery application might query the device to determine its location so that it can render a particular service

1 depending on where the device is located. For example, if the user asks the
2 application to locate the nearest color printer, the service discovery application
3 might query the location service module to ascertain the device's current location
4 so that it can use this information and find the nearest color printer. Consider also
5 that the Outlook application could configure itself email to a work location (when
6 an individual is at work) or to a home location (when an individual is at home). In
7 addition, the Outlook calendar can become location aware, e.g. when you change
8 time zones, your appointments would show up in the proper time slots.

9 As one can imagine, the possibilities are seemingly endless. This
10 functionality is made possible through the use of the Master World and one or
11 more Secondary Worlds.

12 13 **Application Program Interface/Events**

14 In the described embodiment, the applications 608 communicate with the
15 location service module 602 through one or more application program interfaces
16 (APIs) and/or events. The applications can make function calls on the API to
17 query the location service module as to its current location. Similarly, the
18 applications can register for location notifications by using an events registration
19 process. For example, an application may register for a notification when the user
20 changes their location. Consider the case where an application requests to be
21 notified when the user arrives at work or at home so that the application can
22 change the device's configuration (such as printer configuration).

23 Fig. 9 is a flow diagram that describes steps in a method in accordance with
24 the described embodiment. The steps that are described are implemented by
25 device 600. Step 900 receives information that pertains to the current context of

1 the device. In this particular example, a portion of the information is received
2 from one or more context providers which, in this case, are location providers.
3 Step 902 processes the information on and with the device to ascertain the current
4 context of the device. In the illustrated example, the device maintains (or has
5 access to) one or more of the Master World and one or more Secondary Worlds.
6 When the device receives all of the location information, it maps the information
7 to a particular node in the hierarchical tree structure that defines the Worlds. It
8 then traverses the tree structures to ascertain the complete context (i.e. location) of
9 the device. Step 904 receives calls from one or more applications that request
10 information that pertains to the device's current context or location. In the
11 illustrated example, the applications can call one or more APIs to request the
12 information or the applications can register for event notifications. Step 906 then
13 supplies the applications with at least some information that pertains to the current
14 device location. As will be discussed below, a security policy or privacy policy
15 can be applied to the information before it is returned to the applications.

17 **Privacy Manager**

18 In one embodiment, a privacy manager 704 (Fig. 7) is provided. Although
19 the privacy manager is illustrated as being incorporated on the device, it could be
20 implemented by a trusted entity such as a trusted server that is not part of the
21 mobile computing device. The privacy manager can be implemented in any
22 suitable hardware, software, firmware or combination thereof. In the illustrated
23 example, the privacy manager comprises a software module that is incorporated in
24 the mobile computing device.

1 The privacy manager 704 addresses privacy concerns that are associated
2 with the information that is collected by the computing device. Specifically, the
3 location service module can calculate detailed information regarding the location
4 of the computing device. It may be desirable, in some instances, to filter the
5 information that is provided to various applications. That is, it is entirely likely
6 that a user may not want their specific location information provided to untrusted
7 applications. In these instances a user might just desire for location service
8 module 602 to inform such applications that the user is in the State of Washington.

9 Fig. 10 shows a flow diagram that describes steps in a privacy protection
10 method in accordance with the described embodiment. These steps can be
11 implemented by the privacy manager 704.

12 Step 1000 defines a plurality of privacy levels. Exemplary privacy levels
13 are set forth in the table immediately below:

14

15 Privacy Level	Approximate Scale	Level of Revelation
16 0	-	No location information is returned
17 10	100,000 Km	Planet/Continent
18 20	1,000 Km	Country
19 30	100 Km	State
20 40	10-100 Km	City & County or Region
21 50	10 Km	Postal Code & Phone Area Code
22 60	1 Km	Full Postal Code (Zip + 4) & Area Code and Exchange
23 70	100 m	Phone Number & Building/Floor

24
25

80	10m	Room #
90	1m	Exact Coordinates

In the illustrated table, 10 different privacy levels are defined and each has an associated approximate scale. For example, a privacy level of 0 means that no location information is returned. A privacy level of 90 means that very detailed location information is returned.

Step 1002 assigns various privacy levels to the individual nodes in one or more hierarchical tree structures. For example, each node of the Master World and the Secondary Worlds can have a privacy level associated with it. The root node of the Master World tree structure might have a privacy level of 10, while the node that represents a current location in a Secondary World might have a privacy level of 90. Step 1004 determines the context of the computing device. In the present example, the context is the device location and examples of how this is done are given above. Individual applications that call the location service module can have privacy levels associated with them. These privacy levels can be assigned by individual users. For example, a trusted application might have a privacy level of 90, while an untrusted application might have a privacy level of 30. Step 1006 receives context queries from one or more applications. Here, an application calls the location service module 602 (Fig. 7) to ascertain the location of the device. Step 1008 determines the privacy level associated with the application or applications. For example, if a untrusted application calls to request location information, the privacy manager 704 would determine that the application has a privacy level of 30. The privacy manager then traverses (step 1010) one or more hierarchical tree structures to find a node with a corresponding privacy level so

1 that it can select the information that is associated with that node. In this example,
2 the traversal might involve jumping from the Secondary World to the Master
3 World to find the node that corresponds to the state in which the user is located.
4 Once the corresponding node is found, step 1012 returns the context information
5 (e.g. location information) associated with the node. In this case, the location
6 service module would inform the application that the user's location is the State of
7 Washington.

8 As an example, consider the following: There is a web site that gives up to
9 the minute weather of various locations. Accordingly, you might assign this web
10 site a privacy level of 60 so that you can receive weather information for the
11 geographical area that corresponds to your present full postal code. Another web
12 site might be a corporation intranet web site that is a trusted web site. Thus, any
13 applications associated with this web site can be assigned a privacy level of 90 so
14 that you can give them precise location information as to your whereabouts.

15 Thus, in the present example, the computing device is able to determine the
16 source (i.e. application) of its queries and modulate the information that is returned
17 to the application as a function of the application's identity. The computing device
18 is able to do this because it has access to the Master World and one or more
19 Secondary Worlds. The above description constitutes but one exemplary way of
20 accomplishing this feat.

21 22 **Location Beacons as a Location Provider**

23 In one embodiment, one of the location providers comprises a location
24 beacon that beacons or transmits information to enable a computing device to
25 actively participate in its current context. Location beacons can comprise

1 standalone devices that can be retrofitted onto existing infrastructures, e.g. a
2 smoke detector or wall outlet in order for the device to have a power source.

3 Fig. 11 shows an exemplary beacon 1100 that is mounted on a structure
4 1102. Structure 1102 can be any suitable structure such as a wall in a conference
5 room or public place, a smoke detector, an electrical socket and the like. In the
6 described embodiment, the location beacons are small inexpensive devices that
7 can be permanently mounted in special locations such as conference rooms,
8 building lobbies, airport gates, public places and the like. The beacons announce
9 the physical location in the form of an EID and/or LUID to all mobile devices that
10 are within range, such as laptops, tablet PCs, hand held computers, mobile phones,
11 wearable computers and the like.

12 In the described embodiment, the location beacon can identify the particular
13 locations by beaconing standard information that will be understood by the mobile
14 computing devices. In the present example, the beacons can transmit one or two
15 location identifier pairs comprising an EID/URL pair and a LUID/URL pair. The
16 beacon might also transmit multiple LUIDs. The EID and LUID give the present
17 node location in the Master World and Secondary World respectively. The URLs
18 provide a reachable location for the Master and Secondary Worlds. For example,
19 the URL associated with the Secondary World can give a service location that the
20 device can use to query information about the Secondary World so that it can
21 derive its context and take advantage of resources or services that are associated
22 with the nodes in the Secondary World.

23 The beacons can also transmit a digital signature that can be used by the
24 device to ascertain that the beacon is valid and legitimate. Any suitable signature
25 or verification method could be used. In addition, and of particular use in the

1 context-aware environment, the beacon can be programmed to transmit code
2 download pointers to devices within range. The code download pointers can
3 enable the computing device to access software code that permits them to interact
4 with their environment. Consider the following example: You walk into a
5 conference room with your cell phone computing device and immediately a
6 beacon in the conference room transmits your location in the form of an EID/URL
7 pair and a LUID/URL pair. Your device uses the information pairs to ascertain its
8 location in the Master and Secondary Worlds as described above. The beacon also
9 transmits a code download pointer that points to software code that enables you to
10 operate the video projector in the conference room using your hand-held cellular
11 phone. In this manner, the beacon serves as more than just a location beacon—it
12 permits you, through your computing device, to actively participate in your
13 surroundings.

14 The beacons can transmit the information in any suitable way, e.g. wireless
15 methods including infrared and radio frequencies. In one embodiment, Bluetooth
16 short range radio frequency communication can be used to provide a low cost, low
17 power alternative.

18 19 **Cell Phone Embodiment**

20 Within the past several years, cell phones have become a very important
21 communication device. Their prevalence has helped people communicate with
22 one another from seemingly anywhere and at anytime. Today, cell phone
23 functionality permits one to check and send e-mail, browse the Web, send/receive
24 short messages (SMS), leave voice messages and, of course, talk.
25

1 Today, however, cell phones are not aware of their context and in particular,
2 their location. Using the inventive systems, structures and methods described
3 above, cell phones can be imparted with context awareness and location awareness
4 in a way never before experienced. This, in turn, leads to an enhanced user
5 experience. It is to be appreciated and understood that the techniques described
6 above constitute but one way of enabling a cell phone to determine its context
7 and/or location. Other techniques can, of course, be used without departing from
8 the spirit of the claimed subject matter. That is to say, any suitable way, technique,
9 or method can be used to provide a cell phone with, or otherwise enable a cell
10 phone to determine its current context or location.

what is it?
different?

11 Fig. 12 shows an exemplary cell phone 1200 that includes a display area
12 1202, various buttons 1204 that permit a user to interact with the cell phone, and
13 an antenna 1206 for facilitating communication between the cell phone and the
14 outside world.

15 Fig. 13 shows a block diagram of exemplary electronic circuitry of a typical
16 cell phone. The circuitry includes control circuitry 1300 that can include one or
17 more microprocessors, storage or memory 1302 (e.g., ROM, RAM etc.), an
18 antenna 1304, transmit/receive circuitry 1306, a speaker 1308, a microphone 1310,
19 and a ringer/vibrator 1312. The control circuitry 1300 controls transmission and
20 reception of call and voice signals. During a transmission mode, control circuitry
21 1300 provides a voice signal from microphone 1310 to the transmit/receive
22 circuitry 1306. The transmit/receive circuitry 1306 transmits the voice signal to a
23 remote station (e.g., a fixed station, operator, other cellular phones, etc.) for
24 communication through the antenna 1304. The ringer/vibrator 1312 is coupled to
25 the control circuitry 1300, and is used to signal an incoming call to the user. The

1 ringer/vibrator 1312 can emit a ringing or buzzing sound and/or tactile vibrations
2 to indicate an incoming call.

3 During a receiving mode, on the other hand, the transmit/receive circuitry
4 1306 receives a voice signal from a remote station (e.g., a fixed station, operator,
5 other cellular phones, etc.) through the antenna 1304. The control circuitry 1300
6 then provides the received voice signal from the transmit/receive circuitry 1306 to
7 the speaker 1308, which provides audible signals for the user's hearing.

8 In the described embodiment, cell phone 1200 (Fig. 12) is a
9 context/location-aware cell phone that is embodied with the capabilities described
10 above. These capabilities permit the cell phone to ascertain its current context or
11 location, and then adapt its behavior to the current context or location.

12 As an example, consider the following: In a movie theater, it is a courtesy
13 to turn off one's cell phone ringer or to place the cell phone in a vibrate mode so
14 that if a call is received, those around the call's recipient are not disturbed. Many
15 people forget to adjust their cell phones when they are in a theater. Accordingly,
16 if a person receives a telephone call, others around that person will be disturbed.
17 Using the inventive techniques discussed above, the movie theater can put a
18 location beacon in place that advertises itself as a specific location or location
19 class. The cell phone, being aware of its location by virtue of the location beacon,
20 can automatically turn its ringer off or reconfigure to vibrate mode.

21 As another example, consider the following: A user has their cell phone at
22 home and has indicated a preference to have their cell calls forwarded to their
23 home telephone because that phone has much better reception. The cell phone
24 detects, through the inventive location service described above, that it is now
25

1 located at home. Accordingly, whenever it receives a telephone call, it
2 automatically forwards the call to the user's home telephone.

3 4 **Exemplary Context/location Aware Cell Phone Architecture**

5 Fig. 14 shows an exemplary cell phone architecture 1400 that can be used
6 to implement the context/location aware cell phone described above and below. It
7 is to be understood and appreciated that the described architecture constitutes but
8 one exemplary architecture that is capable of implementing a context/location
9 aware cell phone. Accordingly, other architectures can be used without departing
10 from the spirit and scope of the claimed subject matter.

11 Architecture 1400 includes a number of components that are similar to or
12 the same as components that are discussed above. Accordingly, these components
13 are not discussed in much detail here. These components include location service
14 module 1406 (which can also be considered as a context service module), location
15 provider interface 1410, location providers 1412, privacy manager 1408.

16 A cell phone settings engine 1404 is provided and is communicatively
17 linked to location service module 1406 and application program interface/cell
18 phone setting module 1402. The cell phones setting engine 1404 is responsible for
19 receiving context or location information from the location service module 1406
20 and responsive thereto, adjusting or otherwise manipulating a cell phone's settings
21 so that the cell phone behaves in a manner that is consistent with acceptable
22 behaviors for a given location. That is, cell phones exhibit behaviors that in some
23 locations might be appropriate and in others would not be. These behaviors
24 include, without limitation, such things as (1) being on or off, (2) having a ringer
25 turned on or off, (3) being in vibration mode as opposed to having a ringer turned

1 on, (4) having low, medium and high pitch volumes, (5) forwarding calls to certain
2 phone numbers, (6) functioning in a pager mode in which voice information is
3 converted into text information, and the like.

4 Consider, for example, item (1) above. In the context or location of an
5 airplane, the majority of the time a cell phone must be off. It is acceptable in such
6 locations to have a cell phone on when, for example, the plane is sitting at the
7 terminal gate. But, as soon as the plane pushes back from the terminal gate,
8 passengers are typically informed by the flight attendants that their cell phones and
9 other electronic apparatus must be turned off. In accordance with the described
10 embodiment, and as described above and below, each cell phone on an airplane
11 can be informed of its context or location, and can then automatically adjust its
12 behavior by turning itself off until it is no longer located on the airplane.
13 Additionally, consider item (2) above. In a movie theater, as noted above, it is
14 common courtesy to turn one's cell phone off or place it in vibrate mode. Yet,
15 many people forget or refuse to do so. Given the techniques and structures
16 described above and below, cell phones that are determined to be in the location of
17 a movie theater can automatically adjust their behavior to conform to acceptable
18 norms.

19 In the described embodiment, cell phone settings and associated location
20 information can be stored on the cell phone itself. Alternately, the cell phone is
21 configured to receive cell phone setting information via application program
22 interface/cell phone settings module 1402. Specifically, in one embodiment, a
23 number of different settings enforcement entities 1418 can be provided that are
24 responsible for transmitting cell phone settings information to cell phones that are
25 in their vicinity. In the described example, such entities can include, without

1 limitation, Blue Tooth entities, location beacons (as described above), diffused IR
2 entities and the like. These entities transmit cell phone settings information that is
3 received by the cell phone via interface 1402. This information is passed to the
4 cell phone setting engine 1404 which then ensures that the cell phones is set to the
5 proper setting.

6 Also included in this architecture is a source of location-based settings
7 1414, and a source of well-defined locations 1416. Location-based settings can
8 come from any suitable source. For example, the settings can come from the
9 settings enforcement entities mentioned above. Alternately, the location-based
10 settings can be stored on the cell phone. Examples of this are given below.
11 Similarly, the well-defined locations 1416 can come from any suitable source
12 either on or off the device.

13 Fig. 15 is a flow diagram that describes steps in a method in accordance
14 with the described embodiment. The method can be implemented in any suitable
15 hardware, software, firmware, or combination thereof. In the illustrated example,
16 the method is implemented in software that is executing on a cell phone. One
17 exemplary software architecture that is capable of implementing this method is
18 described above in connection with Fig. 14. Other architectures can, of course, be
19 used.

20 Step 1500 receives context information that pertains to the current context
21 of a cell phone. Any suitable methods, techniques, or cell phone components can
22 be used to receive this information. In addition, the context information can come
23 from any type and/or number of context providers. Further, the context
24 information can comprise any suitable type of context information. For example,
25 location and user constitute two examples of specific context. The cell phone

1 processes this information and step 1502 modifies the behavior of the cell phone
2 responsive to the context information.

3 4 **Example**

5 Fig. 16 shows an exemplary system 1600 in which a context-aware cell
6 phone is employed. In this system, as the cell phone enters different locations, it
7 determines its location and then modifies its behavior in accordance with
8 behaviors that are acceptable for that location. Alternately, the cell phone can
9 simply receive information that is then used to adjust the cell phone's settings.

10 In the illustrated example, the different locations include a theater 1602,
11 restaurant 1604, work 1606, home 1608, and a sports arena 1610. Notice that for
12 the theater, restaurant, work and sports arena there are location beacons (not
13 specifically designated) that can provide not only location information, but other
14 information such as, but not limited to, cell phone settings. For each illustrated
15 cell phone, there are a number of associated behaviors that can be modified given
16 a particular location.

17 Notice in this example, that at each different location the cell phone
18 exhibits a different behavior or set of behaviors that are appropriate for that
19 location. For example, in the theater 1602, the cell phone ringer is OFF so that
20 other movie patrons are not disturbed. In the restaurant 1604, the ringer is ON but
21 the volume is low so as not to disturb fellow diners. At work, the cell phone is
22 OFF but is in a mode to forward calls to a work number. At home 1608, the cell
23 phone ringer is ON, but it is in a mode to forward calls to the home number. At
24 the sports arena 1610, the ringer is ON and its volume is VERY HIGH. In
25

1 addition, the phone is in vibration mode. This ensures that the user is most likely
2 to receive their calls in the noisy arena.

3 In one embodiment, the association of location and behaviors is simplified
4 through the use of multiple class types and various attributes that are associated
5 with the class types. The class types define certain high level locations types.
6 Each class type's attributes define the behavior of the cell phone when it is in the
7 vicinity of an instance of that class. As an example consider theater 1602 which is
8 an instance of a class type 1. The attributes associated with a class type 1 are that
9 the cell phone ringer is OFF. No other attributes are associated with this class
10 type. Restaurant 1604 is an instance of a class type 2. The attributes associated
11 with this class type are that the cell phone ringer is ON and the volume is LOW.
12 Work 1606 is an instance of a class type 3. Attributes associated with this class
13 type are that the ringer is OFF and calls are automatically forwarded to an office
14 phone. Home 1608 is an instance of a class type 4 whose attributes are that the
15 ringer is ON and calls are automatically forwarded to a home telephone number.
16 Sports arena 1610 is an instance of a class type 5 whose attributes include that the
17 ringer is ON, the volume is VERY HIGH, and vibration mode is ON.

18 Fig. 17 is a flow diagram that describes steps in a method in accordance
19 with the described embodiment. The method can be implemented in any suitable
20 hardware, software, firmware, or combination thereof. In the described
21 embodiment the method is implemented in software. In the discussion that
22 follows, the flow chart comprises two separate but related portions. The portion
23 on the left designated "Location Service" comprises steps that can be implemented
24 by a location service that is not onboard a cell phone. The flow chart portion on
25

1 the right designated "Cell Phone" comprises steps that can be implemented by a
2 context- or location-aware cell phone.

3 Step 1700 defines one or more class types and step 1702 associates
4 attributes with the class types. The class types are intended to describe certain
5 types of locations where, for example, certain cell phone behaviors are desired.
6 The attributes that are associated with the class types define the cell phone
7 behavior that is desired for that class type. Various examples of this are given in
8 Fig. 16. For example, for a class type 1, attributes are that the ringer is turned off,
9 and so on. Step 1704 associates class types with multiple different locations.
10 Each location is associated with a class type. Accordingly, at these locations, cell
11 phone behavior of location-aware cell phones can be governed by the attributes
12 that are associated with that class type. This provides a simple infrastructure for
13 implementing context-aware phones. By utilizing the concept of class types, those
14 individuals who are in charge of overseeing the context-awareness of their
15 particular locations need not be concerned with anything other than selecting the
16 correct class type for their location. They can do this by simply reviewing the
17 attributes that are associated with the different class types and then selecting an
18 appropriate class type.

19 Step 1706 provides information to one or more cell phones regarding a
20 particular class type for a given location. This information can be provided in any
21 suitable manner and is typically provided when the cell phone enters the vicinity
22 of the location. Recall that Fig. 14 described three settings enforcement entities in
23 the form of Blue Tooth, location beacon, and diffused IR entities. These entities
24 can wirelessly transmit the class type information to cell phones that are in their
25 vicinity. Step 1708 provides information to one or more cell phones regarding

1 attributes associated with the particular class type. This step informs the cell
2 phones of the desired settings for that particular location.

3 Step 1710 receives information regarding a particular class type associated
4 with a current cell phone location and step 1712 receives information regarding
5 one or more attributes associated with that class type. It will be appreciated and
6 understood that only the class type or only the attributes can be transmitted to the
7 cell phone. In the former case, the cell phone can maintain in its storage the
8 various settings that are associated with the class types (i.e. such as in a location-
9 based settings store 1414 (Fig. 14)). In the latter case, the cell phone can simply
10 process the attribute information and adjust its settings accordingly. Step 1714
11 modifies the behavior of the cell phone based on the attributes that it receives.
12 Accordingly, the cell phone's behavior is modified in accordance with behaviors
13 that are determined to be appropriate for the cell phone's location.

14 Step 1716 determines if the cell phone has left the current location. This
15 step can be implemented in any suitable way. For example, there may be a
16 separate location beacon near location exits that inform the cell phones that they
17 are leaving the premises. Alternately, the strength of a beacon signal that signals
18 the location may grow weak to a predetermined threshold so that the cell phone
19 knows that it is no longer at the previous location. If step 1716 determines that the
20 cell phone has left its current location, step 1718 reverts the cell phone to its
21 default or previous settings. If, on the other hand, step 1716 determines that the
22 cell phone has not left its current location, the current settings are maintained (step
23 1720).

24 In accordance with the described embodiments, context-aware or location-
25 aware cell phones are provided. These phones can determine their particular

1 context or location and then automatically configure themselves as by adjusting
2 their settings. Doing so ensures that a cell phone's behavior is consistent with
3 behaviors that have been determined to be appropriate for a given location.

4 5 **Conclusion**

6 The embodiments described above provide a uniform, standardized way to
7 enhance the world of context aware computing. The embodiments provide a way
8 for individuals to uniquely experience the world around them by ascertaining their
9 location in the world in a standard way. The embodiments also provide a way for
10 service providers to uniquely position their goods and services in a manner that is
11 sensitive to and appreciates the contexts, e.g. locations, of various consumers of
12 the goods and services. Unique and useful architectures and data structures are
13 employed to facilitate the user's computing experience and provide for an
14 individual-centric experience.

15 Although the invention has been described in language specific to structural
16 features and/or methodological steps, it is to be understood that the invention
17 defined in the appended claims is not necessarily limited to the specific features or
18 steps described. Rather, the specific features and steps are disclosed as preferred
19 forms of implementing the claimed invention.

20
21
22
23
24
25